

INVINCI Metropolis pattern meets or exceeds all Type II requirements of CCC-W-408D and W-101.

Weigh In	cations:Performance:ght (Avg.):20 oz/ly (452 gr/m²)Width:52/54" (132/137 cm)Backing:OsnaburgInstallation:Straight Hang / Random Match Repeat: V: 24" H: 17.66"weights, widths and microventing are available.
 Pass NFF BS4 CAI 	Fire Safety: STM-E84 (GRC) Class A Isses NFPA 286 Corner Burn FPA 101 Life Safety Code S476 Class 0 AN-ULC S102 N13501 (B-S1-d0)
 Phthalate Free Health Product Dee Environmental Prod Meets State of Was Meets California Sec Aggressive manufact Highly cleanable was 	Avironmental and Health: Declaration (HPD) Available oduct Declaration (EPD) Available ashington Building Specification for Indoor Air Quality ection 01350 Indoor Air Quality Standard acturing materials recovery and reuse program vater-based inks rominated Flame Retardants)

USGBC LEED Support:

- Support USGBC Leed v4 Criteria •
- Materials and Resources; Building Product Disclosure
- (includes Recycled Content; Construction Waste Management)
- Indoor Environmental Quality; Low-Emitting Materials

Moisture, Mold and Mildew:

Vinyl wallcovering functions as a vapor barrier. If water or moisture becomes trapped between the wallcovering and wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use of vinyl wallcovering.

A mildew inhibiting agent has been added to help protect against fungal and other microbiological growth. No additives however, will prevent mold growth if moisture is allowed to accumulate and its sources are not eliminated.

Further protection against mold growth may be achieved with Permavent®, a unique microventing technology that literally "breathes," helping manage the mobile moisture in walls.

Warranty:

INVINCI is guaranteed to be free of defects in workmanship and material for five years. For additional details on moisture management, Permavent, warranty and other INVINCI innovations, visit our website at invinciwallcovering.com.